

**YOU BALE AND WE BUY – Baler type overview and charging structure: Customer copy**

	Baler models available (all Dicom machines): <span style="color: red;">Customer copy</span>		
Features & charges	PGV500	PGV650	PGV650P
Platen / Ram force	30 tons	35 tons	35 tons with longer stroke cycle
Cycle time (Seconds)	70	80	38
Bale dimensions (mm)	Width: 1200 Height: 1060 Depth: 810	Width: 1520 Height: 1000 Depth: 810	Width: 1520 Height: 1000 Depth: 810
Bale weight (Kg)	Up to 500 or ½ ton	Up to 600 or 0.6 tons	Up to 650 or 0.65 tons
Power supply requirements	415volt, 16amp, With 3-phase Neutral & Earth	415volt, 16amp, With 3-phase Neutral & Earth	415volt, 16amp, With 3-phase Neutral & Earth
Power protection requirements	Protection via Type D circuit breaker OR Motor Rated fuses	Protection via Type D circuit breaker OR Motor Rated fuses	Protection via Type D circuit breaker OR Motor Rated fuses
Bale ties / wires available	Min: 4 Max: 4	Min: 4 Max: 6	Min: 4 Max: 6
CE Marked & Emergency stop?	YES	YES	YES
Operator's manual supplied?	YES	YES	YES
Machine height (mm)	Minimum: 2950 Maximum: 3265	Minimum: 2950 Maximum: 3265	Minimum: 3515 Maximum: 3515
Load opening dimensions (mm)	Opening height: 680 Opening width: 1200	Opening height: 680 Opening width: 1520	Opening height: 680 Opening width: 1520
Min safe floor space required for install	6.25 square meters (Approx. 2.5m x 2.5m)	8.75 square meters (Approx. 2.5m x 3.5m)	8.75 square meters (Approx. 2.5m x 3.5m)
Bale door opening clearance (mm)	1320	1550	1550
Motor size and control voltage	5.5kw 24volts	5.5kw 24volts	5.5kw 24volts
Minimum reqd. agreement duration	<span style="color: red;">60 months</span>	<span style="color: red;">60 months</span>	<span style="color: red;">60 months</span>